



## Air Curtain Supply Plenum (ASP)

Provide Accurex Air Curtain Supply Plenum as shown on plans and in accordance with the following specification:

\*\*\*\*\*

Note to User: This document is subject to copyright protection and is proprietary to Accurex Engineered Restaurant Systems. However, Accurex Fan Corporation authorizes the user a limited non-exclusive license to use this document or portions of it for the purpose of preparing written product specifications. All information in this document as provided by Accurex Fan Corporation is informational in nature and is provided without representation or warranty of any kind as to the user or any other party, including, without limitation, ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR PARTICULAR PURPOSE, OR NON-INFRINGEMENT. To the greatest extent permitted by applicable law, Accurex Fan Corporation assumes no liability, and User assumes all liability and risk, for the use or results from the use of this document or the information contained herein, whether as modified by the user or not. Users should consult [www.accurex.com](http://www.accurex.com) to verify that this document represents the most current version.

\*\*\*\*\*

The external air curtain, Accurex model ASP, shall be constructed with a minimum of 18 gauge 400 series stainless steel (300 series optional). Two layers of perforated panels will allow for well distributed low velocity airflow at discharge. Air curtain supply plenums are available in lengths from 3 feet to 16 feet; additional lengths will require hanging multiple plenums. The ASP shall be 14 inches wide by 10 inches high or 24 inches wide by 10 inches high and shall be mounted 14-20 inches above the bottom edge of the hood or flush with a drop ceiling; External air curtain supply plenums can supply airflow at a maximum rate of 180 cfm/ft. For optimum performance, design to the recommended rate of 110 cfm/ft for 14 inch wide plenums or 145 cfm/ft for 24 inch wide plenum.. In addition, external plenums can be attached to the face or ends of an exhaust only hood to create a curtain of air on all exposed sides of the hood, increasing the volume of air brought in at the hood.

Due to continuous research Accurex reserves the right to change specifications without notice.