



Back Supply Plenum (BSP)

Provide Accurex Back Supply Plenum as shown on plans and in accordance with the following specification:

Note to User: This document is subject to copyright protection and is proprietary to Accurex Engineered Restaurant Systems. However, Accurex Fan Corporation authorizes the user a limited non-exclusive license to use this document or portions of it for the purpose of preparing written product specifications. All information in this document as provided by Accurex Fan Corporation is informational in nature and is provided without representation or warranty of any kind as to the user or any other party, including, without limitation, ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR PARTICULAR PURPOSE, OR NON-INFRINGEMENT. To the greatest extent permitted by applicable law, Accurex Fan Corporation assumes no liability, and User assumes all liability and risk, for the use or results from the use of this document or the information contained herein, whether as modified by the user or not. Users should consult www.accurex.com to verify that this document represents the most current version.

The back supply plenum, Accurex model BSP shall be constructed with a minimum of 18 gauge 400 series stainless steel (300 series optional). A layer of perforated panel allows for well distributed low velocity airflow at discharge behind and below the cooking battery. Back supply plenums are available in lengths from 3 feet to 16 feet; where additional lengths require hanging multiple plenums. The BSP is 6 inches wide and discharges 31.25 inches above the finished floor. This plenum is mounted 31.25 inches above the finished floor and directs air flow through perforated panels behind and below the cooking equipment without affecting capture and containment, cooking surface temperature, or pilot lights. Plenums shall be 6 inches deep and stretch the entire length of the hood. They function as a backsplash panel and provide the proper clearance to limited combustibles needed in most circumstances. Back supply plenums are able to supply a maximum of 250 cfm/ft. For optimum performance, design to the recommended rate of 145 cfm/ft.

Due to continuous research Accurex reserves the right to change specifications without notice.