



## Variable Supply Plenum (VSP)

Provide Accurex Variable Supply Plenum as shown on plans and in accordance with the following specification:

\*\*\*\*\*

**Note to User:** This document is subject to copyright protection and is proprietary to Accurex Engineered Restaurant Systems. However, Accurex Fan Corporation authorizes the user a limited non-exclusive license to use this document or portions of it for the purpose of preparing written product specifications. All information in this document as provided by Accurex Fan Corporation is informational in nature and is provided without representation or warranty of any kind as to the user or any other party, including, without limitation, ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR PARTICULAR PURPOSE, OR NON-INFRINGEMENT. To the greatest extent permitted by applicable law, Accurex Fan Corporation assumes no liability, and User assumes all liability and risk, for the use or results from the use of this document or the information contained herein, whether as modified by the user or not. Users should consult [www.accurex.com](http://www.accurex.com) to verify that this document represents the most current version.

\*\*\*\*\*

The variable supply plenum, Accurex model VSP, shall be constructed with minimum of 18 gauge 400 series stainless steel (300 series optional). A manual damper shall be included in the plenum to modulate airflow between the face and air curtain allowing 0 to 50 percent through the air curtain and 50 to 100 percent through the face. Variable supply plenums are available in lengths from 3 feet to 16 feet; additional lengths require hanging multiple plenums. The VSP is 12 inches wide by 18 inches high. Perforated panels shall be included to reduce air velocities and eliminate spillage from the hood. Variable supply plenums are able to supply a maximum of 275 cfm/ft. Supply rates should be designed to recommended values of 150 cfm/ft. through the face and 100 cfm/ft. through the curtain for optimum performance.

Due to continuous research Accurex reserves the right to change specifications without notice.